


M H A

POWER TOOLS 

PROFESSIONAL POWER TOOLS

**High Performance Power Tools
from MHA**



Novara_Italy

www.mhatools.com

IMPACT DRILL

MID560



Specification

| | |
|--------------------|-------------|
| Power input: | 560 W |
| No load Speed: | 0-2900 rpm |
| Impact rate: | 0-46400 bpm |
| Chuck: | 13 mm |
| Drilling capacity: | |
| in Concrete: | 13 mm |
| in steel: | 10 mm |
| in wood: | 25 mm |

MID810



Specification

| | |
|--------------------|-------------|
| Power input: | 810 W |
| No load Speed: | 0-2800 rpm |
| Impact rate: | 0-44800 bpm |
| Chuck: | 13 mm |
| Drilling capacity: | |
| in Concrete: | 16 mm |
| in steel: | 13 mm |
| in wood: | 25 mm |

IMPACT DRILL

MID112E



2 Mechanical Speed

Specification

| | |
|--------------------|-------------------------|
| Power input: | 1100 W |
| No load Speed: | 0-2700 rpm 0-900 rpm |
| Impact rate: | 0-46400 bpm |
| Chuck: | 13 mm |
| Drilling capacity: | |
| in Concrete: | 16 mm |
| in steel: | 13 mm |
| in wood: | 30 mm |

MHD650



Specification

| | |
|--------------------|------------|
| Power input: | 650 W |
| No load Speed: | 0-2900 rpm |
| Chuck: | 10 mm |
| Drilling capacity: | |
| in Concrete: | 10 mm |
| in steel: | 7 mm |
| in wood: | 20 mm |

HAND DRILL

ROTARY HAMMER

MRH853



Specification

| | |
|--------------------|----------|
| Power input: | 850 W |
| No load Speed: | 780 rpm |
| Hammer rate: | 3150 bpm |
| Drilling capacity: | |
| in Concrete: | 28 mm |
| in steel: | 13 mm |
| in wood: | 40 mm |

MRH804



Specification

| | |
|--------------------|------------|
| Power input: | 800 W |
| No load Speed: | 0-780 rpm |
| Hammer rate: | 0-3900 bpm |
| Drilling capacity: | |
| in Concrete: | 30 mm |
| in steel: | 13 mm |
| in wood: | 40 mm |

ROTARY HAMMER

MRH113

Specification

| | |
|--------------------|------------|
| Power input: | 1100 W |
| No load Speed: | 0-780 rpm |
| Hammer rate: | 0-3150 bpm |
| Drilling capacity: | |
| in Concrete: | 32 mm |
| in steel: | 13 mm |
| in wood: | 50 mm |



Heavy Duty Shock Absorber

ANGLE GRINDER

MAG230D



Specification

| | |
|------------------------|----------|
| Power input: | 2300 W |
| No load Speed: | 6000 rpm |
| Grinder disc diameter: | 230mm |
| Spindle thread: | M14 |

MAG500 ANGLE GRINDER



Specification

| | |
|------------------------|-----------|
| Power input: | 500 W |
| No load Speed: | 11000 rpm |
| Grinder disc diameter: | 115mm |
| Spindle thread: | M14 |

MAG620/901 ANGLE GRINDER



Specification

| | |
|------------------------|-----------|
| Power input: | 620/900 W |
| No load Speed: | 11000 rpm |
| Grinder disc diameter: | 115/125mm |
| Spindle thread: | M14 |

MAG102 ANGLE GRINDER



Specification

| | |
|------------------------|-----------|
| Power input: | 1010W |
| No load Speed: | 11000 rpm |
| Grinder disc diameter: | 125mm |
| Spindle thread: | M14 |

MAG235 ANGLE GRINDER



Specification

| | |
|------------------------|----------|
| Power input: | 2350 W |
| No load Speed: | 6000 rpm |
| Grinder disc diameter: | 230mm |
| Spindle thread: | M14 |

JIG SAW WITH PENDULUM FUNCTION

MJS570

Option:



Specification

| | |
|------------------------|--------------|
| Power input: | 570 W |
| No load Speed: | 500-3000 rpm |
| Bevel cuts: | 0-45° |
| Max. cutting capacity: | |
| in steel: | 8 mm |
| in wood: | 65 mm |

MCS136

CIRCULAR SAW



Specification

| | |
|--------------------------------------|-----------|
| Power rating: | 1300 W |
| Speed: | 4500 rpm |
| Maximum cutting height: | 90° :50mm |
| | 45° :35mm |
| Carbide metal saw blade: φ160x20x24t | |

MCS127

CIRCULAR SAW



Specification

| | |
|--------------------------------------|-----------|
| Power rating: | 1200 W |
| Speed: | 4500 rpm |
| Maximum cutting height: | 90° :63mm |
| | 45° :40mm |
| Carbide metal saw blade: φ185x20x24t | |

MCS137

Option:



CIRCULAR SAW

Specification

| | |
|---------------------------------------|-----------|
| Power rating: | 1300 W |
| Speed: | 4500 rpm |
| Maximum cutting height: | 90° :65mm |
| | 45° :45mm |
| Carbide metal saw blade: φ185xφ20x24t | |

Multi-purpose Tool



MMT260S



Specification

| | |
|------------------|-----------------|
| Power input: | 260 W |
| Variable speed | |
| Swing frequency: | 11000-21000 opm |
| Swing extent: | 3.2° |



MRS650**RECIPROCATING SAW****Specification**

| | |
|--------------------|----------------|
| Power input: | 650 W |
| No load Speed: | 500 - 3000 rpm |
| Stroke: | 20 mm |
| Drilling capacity: | |
| in Aluminium: | 16 mm |
| in Wood: | 115 mm |
| in Non-alloyed | 10 mm |

MRS850**RECIPROCATING SAW****Specification**

| | |
|--------------------|----------------|
| Power input: | 850 W |
| No load Speed: | 800 - 3000 rpm |
| Stroke: | 24 mm |
| Drilling capacity: | |
| in Aluminium: | 20 mm |
| in Wood: | 210 mm |
| in Non-alloyed | 10 mm |

MEP601**ELECTRIC PLANER****Specification**

| | |
|--------------------|-----------|
| Power input: | 600 W |
| Rated Speed: | 15000 rpm |
| Width of planning: | 82 mm |
| Depth of planning: | 1 mm |

INVERTER TIG WELDING MACHINE**MPW101****Specification**

| | |
|--|-------------------|
| Power input: | 2800 W |
| Input Current: | 15.8 A |
| No-load Voltage: | 61 V |
| Welding Current range: | 5-100 A |
| Rated Duty Cycle(25°C 10 min): | 45%@100A 100%@90A |
| (40°C 10 min): | 30%@100A 100%@60A |
| Electrode diameter: | Ø3.2 mm |
| Adopt IGBT & advanced PWM inverter technology | |
| Anti-sticking, arc force, hot start, TIG(Lift) | |

POLISHER

MGP120

Variable speed



Specification

Power input: 1200 W

No load Speed: 1000-3000 rpm

Diameter: 180 mm

POLISHER

MGP130S

Variable speed



Specification

Power input: 1300 W

No load Speed: 900-3000 rpm

Diameter: 180 mm

MGW110

WAXER

Specification

Rated Power: 110 W

No load Speed: 3200 rpm

Pad size: Φ 240 mm**MGW111**

WAXER

Specification

Rated Power: 110 W

No load Speed: 3200 rpm

Pad size: Φ 240 mm

MES105



Specification

| | |
|----------------|---------------|
| Power input: | 105 W |
| No load Speed: | 12000 rpm |
| Pad size: | 140x140x80 mm |

MES214



Specification

| | |
|----------------|------------|
| Power input: | 210 W |
| No load Speed: | 11000 rpm |
| Pad size: | 110x100 mm |

MES215



Specification

| | |
|----------------|-----------|
| Power input: | 215 W |
| No load Speed: | 12000 rpm |
| Pad size: | 190x90 mm |

Variable speed

MRS450



ROTARY SANDER

Specification

| | |
|----------------|----------------|
| Power input: | 450 W |
| No load Speed: | 4000-11000 rpm |
| Pad size: | φ125 mm |

MBS730**BELT SANDER****Specification**

Power input: 730 W
 No load Speed: 260 m/min
 Sanding size: 76x457 mm

MBS101**BELT SANDER****Specification**

Power input: 1010 W
 No load Speed: 120-380 m/min
 Sanding size: 76x533 mm

MHG152**HOT AIR GUN****Specification**

Power input I: 750 W
 II: 1500 W
 Temperature I: 300°C
 II: 500°C
 Air flow I: 280 l/min
 II: 480 l/min

MAB400**AIR BLOWER****Specification**

Power input: 400 W
 No load Speed: 16000rpm
 Air volume: 2.5m³/min

ROTARY TOOL KITS**MRT135B****Specification**

Power input: 135 W
 No load Speed: 8000-30000rpm



219 pcs set

ROTARY TOOL KITS**MRT135A****Specification**

Power input: 135 W
 No load Speed: 8000-30000rpm



235 pcs set

MPM850



Specification

| | |
|-----------------|-----------|
| Power input: | 850 W |
| No load Speed: | 0-500 rpm |
| Drill capacity: | φ13 mm |
| Mixing Paddle: | φ120 mm |

MPM122



2 Mechanical speed

Specification

| | |
|----------------|-----------|
| Power input: | 1220 W |
| No load Speed: | 0-480 rpm |
| | 0-800 rpm |
| Tool fitting: | M14 x 2 |
| Mixing Paddle: | φ120 mm |

CUT-OFF MACHINE

MCM160



Specification

| | |
|-----------------|----------|
| Power input: | 1600 W |
| No load Speed: | 3600 rpm |
| Blade diameter: | 355 mm |

Miter SAW 210MM

MMS128B



Specification

| | |
|---------------------------|------------------------|
| Power input: | 1500 W |
| No load Speed: | 5000 rpm |
| Blade Dimension: | φ210mm(8") |
| Max. cutting capacity at: | |
| | 0°/90°(H*W): 60°120mm |
| | 0°/45°(H*W): 60°80mm |
| | 45°/90°(H*W): 35°120mm |
| | 45°/45°(H*W): 35°80mm |

BENCH GRINDER

MBG156P



Specification

| | |
|----------------|------------------|
| Power input: | 150 W |
| No load Speed: | 2950 rpm |
| Wheel size: | |
| | φ150x16xφ12.7 mm |

TILE CUTTER

MTC457



Specification

| | |
|----------------------|------------------|
| Power input: | 450 W |
| No load Speed: | 2950 rpm |
| Table tilting range: | 0°- 45° |
| Table size: | 330x360 mm |
| Depth of cut: | 34mm @ 90° |
| Blade size: | φ180xφ22.2x2.2mm |

110MM MARBLE CUTTER

MTC130



Specification

| | |
|-----------------------|-----------|
| Power input: | 1200 W |
| No load Speed: | 12000 rpm |
| Blade diameter: | 110 mm |
| Max cutting capacity: | 34mm |

CHAIN SAW SHARPENAR

MGCS220



Specification

| | |
|-----------------------|-------------------|
| Power input: | 220 W |
| No load Speed: | 7500 rpm |
| Grind wheel diameter: | |
| | ø100xø10x3.4 1/4" |
| | ø100xø10x4.5 3/8" |

DRY BATTERY OPERATE SCREWDRIVER

PBS045



3 x1.5V AA battery



Specification

| | |
|----------------|---------|
| DC voltage: | 4.5V |
| No load Speed: | 200 rpm |

TWIST DRIVER

MU03-36

powerful 3.6V
rugged steel
gears
rechargeable
ergonomic



14 pcs set



Specification

| | |
|----------------|---------|
| DC voltage: | 3.6V |
| No load Speed: | 200 rpm |

PALM PRO

ML01-036

powerful 3.6V
rugged steel
gears
rechargeable
lightweight
ergonomic



Specification

| | |
|----------------|---------|
| DC voltage: | 3.6V |
| No load Speed: | 250 rpm |

CORDLESS DRILL

MCD120
MCD144
MCD180



Specification

| | | | |
|----------------|-----------|-----------|-----------|
| DC voltage: | 12V | 14.V | 18V |
| No load Speed: | 0-550 rpm | 0-550 rpm | 0-550 rpm |
| Chuck: | 10 mm | 10 mm | 10 mm |
| Torque stage: | 20+1 | 20+1 | 20+1 |

CORDLESS DRILL

MU03-120
MU03-144
MU03-180



Specification

| | | | |
|----------------|-----------|-----------|-----------|
| DC voltage: | 12V | 14.4V | 18V |
| No load Speed: | 0-550 rpm | 0-550 rpm | 0-550 rpm |
| Chuck: | 10 mm | 10 mm | 10 mm |
| Torque stage: | 20+1 | 20+1 | 20+1 |

MU03-182

2 Mechanical speed



CORDLESS DRILL

Specification

| | |
|---------------------------|------------|
| DC voltage: | 18V |
| No load Variable Speed: | |
| (Low setting) | 0-350 rpm |
| (High setting) | 1-1000 rpm |
| Heavy duty Keyless chuck: | 3/8"(10mm) |
| Torque stage: | 20+1 |



European Union Quality
Novara_Italy
Info@mhatools.com

www.mhatools.com